

iEvac[®] Demo Hood EBP-200 FOR DEMO PURPOSES ONLY

Please Read Before Donning

1. The iEvac® contains an anti-fog coating. To prevent any fogging, when donning the hood, the individual should hold their breath for the few seconds until the nose cup is secured over their nose and mouth and fits under their chin. To accomplish this they need to quickly pull the straps tight once the nose cup is in position.

2. While being worn it is normal for the iEvac® hood itself to move very slightly in phase with the breathing of the wearer. This small harmonic movement shows that the neck seal is performing correctly and preventing smoke and other materials from by-passing the filters and entering the hood. Most people will not detect it, but the in-andout motion may be pronounced when the hood is worn by larger individuals or when the wearer is breathing very deeply. The protection provided by the iEvac® is not affected by this movement.

3. After each donning of an iEvac® it is to be cleaned and disinfected with a non-alcohol sterilized wipe. All parts of the iEvac® are to be cleaned and disinfected, including the neck seal, the half mask and the interior of the clear visor. Be aware that, due to this sterilization process the antifog coating on the inside of the clear visor may be worn away. As a result some fogging may occur when the iEvac® is donned by subsequent wearers. The anti-fog coating on the clear visor will not deteriorate while the iEvac® is stored inside its sealed package

iEvac[®] Donning Instructions




This hood pulls over your head like a ski mask. Look at the pictures to see how it is worn. Your head goes inside with the cup at the front. The hood opening goes around your neck. You pull the straps tight so that the cup snugly covers your nose and mouth.



1. Quickly tear open the foil bag at the slit marked with a "tear to open" sticker.

Take out and unfold the hood




3. With the nose cup and filters facing down towards your body, stretch the hood opening out by placing your fingers in the neck dam with your thumbs spread wide and the back of your hands facing each other.

4. Place the neck dam under your chin and pull the hood over your head & pull the neck dam down to the bottom of your neck.



IMPORTANT: Immediately make sure the cup is covering your nose and mouth and fits under your chin.




5. Using both hands, quickly grab the ends of the back straps and pull them tight ensuring that the cup fits snugly.



6. Make sure the hood opening directly touches your neck all around.

Removing the iEvac®



1. First lift the tab (protruding end) of one connecting buckle with one hand and with your other hand pull the elastic strap towards the front.

2. Repeat with the second buckle and strap.

3. Pull the iEvac® over your head.



Elmridae 1200 Clint Moore Rd. Unit #15, Boca Raton, FL 33487 561.244.8337 · Info@ElmridgeProtection.com ElmridgeProtection.com